



kramer

C-CU32/UC+H

Active Multi-Format Input (M) to USB C
Output (M) Adapter Cable



C-CU32/UC+H is an active multi-format male input to USB-C male output adapter that enables you to connect HDMI + USB 3 or USB Type-C source (Laptop) to an USB-C acceptor (monitor or switcher). The adaptor supports full USB-C 3.2 features (when the input is HDMI, need to connect the USB 3.2 A type connector).

The adaptor is perfect for BYOD meeting rooms as direct connection between the Laptop to the USB-C monitor, or in a big meeting room by connecting it between the laptop to the under the desk USB-C switcher (for example, SWT3-31-HU-TR, it's recommended to set the input EDID to 4K@30 4:4:4).

Note: Devices connected to the C-CU32/UC+H USB-C Output, require their own power source.

Note: Compatible with PG-U32/FF (sold separately) for laptops with tightly spaced USB-C ports or a large gap between the port and desk surface

FEATURES

High-Performance Adapter Cable - Supports full 4K@30Hz digital video connectivity

Active Adapter - Retimes the signal to ensure full resolution signal quality

Simplifies Equipment Requirements - Replaces multiple separate cables, adapters, and dongles with a single multi-head cable

Plug and Play Installation - No software required

2.7 Meter Output Cable



kramer

TECHNICAL SPECIFICATIONS

Inputs	HDMI: On a male HDMI connector + USB 3.2 A type 40cm (15.7") pigtail USB-C: On a male USB type-C Connector
Video	Max Resolution: Up to 4K@30Hz 4:4:4
Power	60W (when the input is USB-C)
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety: FCC, CE Environmental: RoHs, WEEE
Enclosure	Type: ABS Shell
General	Product Dimensions: W, D, H 9.2cm x 8.3cm x 1.2cm (3.6" x 3.2" x 0.47")

